NOTES:

1. DRAWING TO BE INTERPRETED IN ACCORDANCE WITH THE CURRENT REVISION OF ASME Y14.5.
2. THIS PART/PRODUCT IS TO BE MANUFACTURED WITH THE LATEST APPLICABLE REGULATIONS OF EC DIRECTIVES FOR THE RESTRICTION OF THE USE OF HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT (ROHS), WASTE ELECTRICAL AND ELECTRONIC EQUIPMENT (WEEE) AND REGISTRATION, EVALUATION, AUTHORIZATION AND RESTRICTION OF CHEMICALS (REACH).
3. OUTPUTS ARE FROM THE CENTER TO THE FULL TRAVEL POSITION.
   OPTIONS "AA", "BB", "CC", "DD", "EE", "FF" PROVIDE INCREASED VOLTAGE IN +Y; AND DECREASING VOLTAGE IN -Y DIRECTION FROM ONE OUTPUT PER AXIS.
   OPTIONS "GG" AND "HH" PROVIDE INCREASING VOLTAGES.
   IN ALL DIRECTIONS (+Y, -Y) FROM 2 OUTPUTS PER AXIS.
4. OPTIONS "BB" AND "EE" PROVIDE REDUNDANT OUTPUT 2 WHICH DUPLICATES OUTPUT 1.
   OPTIONS "CC" AND "FF" PROVIDE REDUNDANT OUTPUT 2 WHICH IS INVERSE OF OUTPUT 1.
5. SEE PAGE 3 FOR ALTERNATE BUTTON DESIGN. ONLY BUTTON STYLE "2", "5", AND "6" ARE OFFERED WITH A WATERTIGHT PANEL SEAL.
6. MARKING TO INCLUDE:
   "OTTO" P/N & DATE CODE "YYWW".

HTL2-

5 BUTTON STYLE	CASE STYLE	5 SEAL	TRAVEL	GATING	OPERATE FORCE	OUTPUT 1 3	OUTPUT 2 4	TERMINATION	BUTTON COLOR
1 = CASTLE 2 = EXTERNAL CASTLE BOOT 3 = SHORT DOUBLE STADIUM 4 = TALL CONCAVE STADIUM 5 = EXTERNAL BAT HANDLE BOOT 6 = EXTERNAL SMOOTH BOOT 7 = LONG CONCAVE Y AXIS BUTTON	1 = .970 SQ.	1 = DUSTTIGHT 2 = WATERTIGHT	1 = 25 DEGREES	1. SINGLE AXIS	1 = 16 OZ	AA = 2.5+/-2.0 VDC BB = 2.5+/-2.0 VDC CC = 2.5+/-2.0 VDC DD = 2.5+/-1.5 VDC EE = 2.5+/-1.5 VDC FF = 2.5+/-1.5 VDC GG = 0.5-4.5 VDC HH = 1-4 VDC	NONE 2.5+/-2.0 VDC 2.5-/+2.0 VDC NONE 2.5+/-1.5 VDC 2.5-/+1.5 VDC 0.5-4.5 VDC 1-4 VDC	1 = WIRE LEADS, 22 AWG, UL1569 2 = PINS 3 = WIRE LEADS, 24 AWG, SAE AS22759	2 = BLACK

HTL2-_____

REV	OCN #	DATE	APR
A	044213	17 JUL 08	LBG
B	046891	19 JAN 09	LBG
C	063013	19 SEP 11	DCF
D	063582	28 OCT 11	KLW
E	066712	27 JUL 12	DCF
F	070736	31 MAY 13	DCF
G	071505	08 AUG 13	DCF

PRODUCT SPECIFICATIONS

ELECTRICAL:

RATED AT Vcc = 5V @ 20°C LOAD = 1ma (4.7KΩ)	UNITS	MIN	TYP	MAX
SUPPLY VOLTAGE, Vcc	VDC	4.50	5.00	5.50
OUTPUT VOLTAGE TOLERANCE AT CENTER (SEE APPROPRIATE GRAPH FOR OUTPUT VALUES)	VDC @5V Vcc	-.25	NA	+.25
OUTPUT VOLTAGE TOLERANCE FULL TRAVEL (SEE APPROPRIATE GRAPH FOR OUTPUT VALUES)	VDC @5V Vcc	-.25	NA	+.25
SUPPLY CURRENT PER SENSOR B=0, Vcc=5V, Iout=0	mA	NA	NA	10.0
OUTPUT SOURCE CURRENT LIMIT B=-X*, Vo=0	mA	-1.00	NA	1.00
OUPUT RESISTANCE Io < -2 mA	Ω	NA	1.00	10.00

MECHANICAL:


MECHANICAL LIFE ALL DIRECTIONS	1,000,000 CYCLES			
TRAVEL ANGLE	DEGREES	23	25	27
OPERATING FORCE (W/BOOT) AT TOP OF BUTTON, @ 20°C	OZ	NA	16	20
MAX. ALLOWABLE VERTICAL FORCE ON BUTTON	LBS	NA	NA	25
MAX. ALLOWABLE RADIAL FORCE ON BUTTON	LBS	NA	NA	25
MAX. ALLOWABLE TORQUE ON BUTTON ABOUT SHAFT AXIS	IN-LBS	NA	NA	5.5 (G)

ENVIRONMENTAL:


OPERATING TEMPERATURE	°C	-40	20	85
ELECTRONICS SEAL INTEGRITY	WATERTIGHT PER IP68S, 1 METER			
EMI/RFI WITHSTAND	PER SAE J1113 CONTACT FACTORY FOR DETAILS			


MATERIAL:

BOOT	ELASTOMER, BLACK
BUTTON	THERMOPLASTIC, BLACK
CASE	THERMOPLASTIC, BLACK
FLANGE	THERMOPLASTIC, BLACK
HARDWARE	4X ITW FASTEX PANEL FASTENER P/N 36030002, OR EQUIVALENT





PINS NOT PRESENT IN ALL CONFIGURATIONS








SCALE 1:1













DETAIL A

SCALE 4:1

ALL PINS NOT PRESENT IN ALL CONFIGURATIONS



SUGGESTED PANEL OPENING



SHIPPED UNASSEMBLED

ALL WIRES NOT PRESENT IN ALL CONFIGURATIONS

OUTPUT2 NOT PRESENT IN ALL CONFIGURATIONS

KEY CHARACTERISTICS

SR SPECIAL REQUIREMENT

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES.
TOLERANCES:
.XX ±.03
.XXX ±.010
ANGLES ±2°
DO NOT SCALE

OTTO
CARPENTERSVILLE, ILLINOIS USA


THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF OTTO ENGINEERING, INC.. IT IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF OTTO ENGINEERING, INC..

DESCRIPTION
HTL2, LINEAR HALL EFFECT
2-WAY TOGGLE


DRWN. JLW	SIZE	FSCM NO	DRAWING NO.	REV.
CHKD. MRM	C	21649	HTL2-_____	G
APPD. AH				

THIRD ANGLE PROJECTION | Scale 1:1 | Sheet 1 OF 4


OPTION AA




OPTION BB




OPTION CC




OPTION DD




OPTION EE




OPTION FF



OPTION GG



OPTION HH





UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES ARE AS LISTED. MUST BE FREE FROM BURRS AND SHARP EDGES


TOLERANCES
.XX ±.03
.XXX ±.010
ANGLES ±2°
DO NOT SCALE DRAWING


THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF OTTO ENGINEERING, INC.. IT IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF OTTO ENGINEERING, INC..


DRWN. JLW	SIZE	FSCM NO	DRAWING NO.		REV.
CHKD. MRM	C	21649	HTL2-_____		G
APPD. AH					
WT.	THIRD ANGLE PROJECTION		Scale 1:1	Sheet 2 OF 4	




















BUTTON STYLE 1
(CASTLE)


BUTTON STYLE 2
(EXTERNAL CASTLE BOOT)

BUTTON STYLE 3
(SHORT DOUBLE STADIUM)


BUTTON STYLE 4
(TALL CONCAVE STADIUM)

BUTTON STYLE CONFIGURATION


UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES ARE AS LISTED. MUST BE FREE FROM BURRS AND SHARP EDGES	TOLERANCES .XX ±.03, .XXX ±.010, ANGLES ±2° DO NOT SCALE DRAWING	THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF OTTO ENGINEERING, INC.. IT IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF OTTO ENGINEERING, INC..	DRWN. JLW / CHKD. DCF / APPD. AH / WT.	SIZE C	FSCM NO 21649	DRAWING NO. HTL2-_____	REV. G
					THIRD ANGLE PROJECTION	Scale 1:1	Sheet 3 OF 4



BUTTON STYLE 5
(EXTERNAL BAT
HANDLE BOOT)



BUTTON STYLE 6
(EXTERNAL SMOOTH BOOT)



BUTTON STYLE 7
(LONG CONCAVE Y AXIS BUTTON)

BUTTON STYLE CONFIGURATION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES ARE AS LISTED. MUST BE FREE FROM BURRS AND SHARP EDGES	TOLERANCES .XX ±.03 .XXX ±.010 ANGLES ±2° DO NOT SCALE DRAWING	THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF OTTO ENGINEERING, INC.. IT IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF OTTO ENGINEERING, INC..	DRWN. JLW CHKD. DCF APPD. AH WT.	SIZE C	FSCM NO 21649	DRAWING NO. HTL2-_____ REV. G THIRD ANGLE PROJECTION Scale 1:1 Sheet 4 OF 4

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

OTTO:

HTL2-212111AA12 HTL2-212111DD12 HTL2-312111AA22 HTL2-312111BB12 HTL2-512111AA12 HTL2-512111CC12 HTL2-711111GG12 HTL2-712111AA22 HTL2-512111GG12 HTL2-112111AA12 HTL2-312111DD12 HTL2-312111GG12 HTL2-111111CC22 HTL2-212111AA22 HTL2-711111AA12 HTL2-712111CC22 HTL2-711111CC12 HTL2-111111BB22 HTL2-112111CC12 HTL2-212111BB12