Product data sheet Characteristics

XVEC35

\varnothing 70 mm illuminated unit - steady - orange - up to IP42 - <= 240 V

luminance: 640 cd/m²

Bulb type

[Us] rated supply volt-



Main	
Range of product	Harmony XVE Optimum
Product or component type	Indicator bank
Beacon or indicator bank unit type	Illuminated unit
Signalling type	Steady
Component name	XVE
Light source	Orange bulb not included

<= 240 V AC/DC

Incandescent with BA 15d base

Complementary

Mounting diameter	70 mm	
Assembly style	Customer assembly	
Power dissipation in W	≤ 5 W	
Connections - terminals	Screw clamp terminals : <= 1 x 1.5 mm² with cable end	
Marking	CE	
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1	
Nominal voltage limit	0.851.1 Un conforming to IEC 60947-5-1	
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-1	
Luminance	640 cd/m²	
Product weight	0.072 kg	

Environment

Standards	EN/IEC 60947-1
	EN/IEC 60947-5-1
Product certifications	CCC
	CSA
	UL
Ambient air temperature for storage	-4070 °C
Ambient air temperature for operation	-2555 °C
Class of protection against electric shock	Class I aluminium tube mounting conforming to IEC 61140
	Class I plastic tube mounting conforming to IEC 61140
Protective treatment	TC
IP degree of protection	IP40 in any position except vertical position conforming to IEC 60529
	IP42 in vertical position conforming to IEC 60529
RoHS EUR conformity date	0914
RoHS EUR status	Compliant