







The uEZ GUI® unit is everything you need right out of the box to have a touch screen GUI instantly in your project.

Each uEZ GUI unit is available in two convenient forms. To get your project started quickly we offer a full development kit complete with JTAG debugger, power supply, cables, a microSD card and full documentation. The Dev Kit Part Number is **uEZGUI-4088-43WQN**. Once your design is complete, we also offer a cost-effective production module for prototypes or even for high volume production. The module includes the touchscreen display, all of the necessary hardware, and is supported by the uEZ® / FreeRTOS™ open source software. The uEZ GUI module is available off-the-shelf from any of our franchised distributors under Part Number **uEZGUI-4088-43WQN-BA**.



Features

- 4.3" TFT WQGA 480 x 272 LCD Panel with Projected Capacitive Touch Screen
- NXP LPC4088 120MHz CPU with 512KB internal Flash
- · 16MB SPIFI Serial Flash
- 8MB of SDRAM (optional to 32MB)
- High Speed SD interface supporting 15fps video playback
- · 4GB microSD Memory Card
- USB Device Mini-AB for 5.0VDC power and PC communications
- USB Host support through adapter cable
- NV Data Storage via 4KB Internal EEPROM
- Internal Real-Time Clock with Supercap Backup
- Speaker, 3-axis Accelerometer, Temperature Sensor
- PMOD Type 2A connector with SPI and optional I2C
- · Mini-JTAG Debug Connector
- External Expansion via two I/O Connectors (70 pins)
 - UART, I2C, SPI, USB Host/Device, RMII Ethernet



















4.3" Capacitive Touch Screen LCD GUI

Module Specifications

- Module P/N: uEZGUI-4088-43WQN-BA
- Contrast Ratio: 500 typical
- Luminance: 340 cd/m2 typical
- Viewing Angle Horizontal: 70° L / 70° R
- Viewing Angle Vertical: 70° U /50° D
- Power consumption typ/max: 350/500mA @ 5.0VDC
- Operating Temperature Range: -20°C to +70°C

- Overall Size: 4.60"W x 2.84"H x 0.56"T
- Viewable area: 3.74"W x 2.12"H
- · Weight: 103g
- Touch Resolution: 480x272
- Number Simultaneous Touches:1
- Glass Overlay: 0.7mm
- Glass Hardness: 6H

The **uEZGUI-4088-43WQN-BA** is the stand alone System On Module version and is priced at less than \$175.00 in volume. This unit is designed to be used as an "off-the-shelf" Graphical User Interface (GUI) or Human Machine Interface (HMI) in a variety of end customer applications. The miniature, self-contained design is well suited to embed directly into your product or FDI offers prepackaged versions. FDI also offers low cost customization services for customer specific hardware, software or packaging applications at volumes of 500 units or more.

Software

μΕΖ° (pronounced Muse) is an open source rapid development platform that supplies application developers with an extensive library of open source software, drivers, and processor support - all under a common framework. μΕΖ° allows companies to focus on innovation and their value-added applications while minimizing development time and maximizing software reuse.

The diagram to the right shows a typical embedded application stack. The μEZ° components comprise three primary categories to simplify embedded application development:

- Operating System Abstraction Layer (μΕΖ® OSAL)
- Sub-system drivers (ex: μΕΖ® TCP/IP, μΕΖ® USB, μΕΖ® Driver)
- Hardware Abstraction Layer (µEZ® HAL)

Software Included:

- uEZ® / FreeRTOS Rapid Development Platform
- uEZ® / SafeRTOS option for Medical/Safety Apps
- MicroSD card maps as USB Flash Drive to the PC
- Rowley CrossWorks Compiler and Tool Suite
- Segger J-Link Lite JTAG for programming and debug
- Customized versions available

FreeRTOSTM | Free

Applications



Kit Contents

Ordering Information

Kit Part Number: uEZGUI-4088-43WQN Suggested Resale Price: \$319.00(USD) Order Online at: www.uEZGUI.com or from any of our franchised distributors

Warranty: 30-day money back guarantee Phone 256-883-1240 Fax 256-883-1241 sales@teamfdi.com

Kit Contents:

- uEZGUI-4088-43WQN-BA Production Module
- USB Device cables for Power and PC communications
- AC Power Supply
- Mini JTAG Debugger with cables
- Micro SD Card

Download Users Manual, documents, schematics, and software examples at: www.teamfdi.com/uEZGUI



www.teamfdi.com (256) 883-1240



@TeamFDI #TeamFDI



Youtube.com/ FDIProducts