2500W 1U Front End Power Supplies

Features

- 1U rackmount containing up to 4 units
- Internal ORing MOSFET & Current Share
- High Efficiency
- Up to 9,500W in 1U rack



Key Market Segments & Applications

Industrial COTS Test COMM Broadcast

PMBus 80 PLUS PLATINUM RoHS

(HFE2500-48 model)

Specifications

Model			
Input Voltage Range	(2)	VAC	85 - 265VAC, 47 - 63Hz. See model selector for power derating
Input Current (Max) 100/230VAC		A	15 / 12A
Inrush Current		A	<50A
Power Factor Correction		-	Meets EN61000-3-2, PF > 0.98 at full load
Temperature Coefficient		%/°C	<0.02%/°C
Overcurrent Protection		%	105 - 115%
Overvoltage Protection	(1)	%	110% (Tracking). Cycle AC to reset or utilize Remote On/Off
Overtemperature Protection	(1)	-	Shutdown with automatic reset. Warning signal provided
Hold-up time		ms	>10ms, 115/230VAC Input, 80% loading
Leakage Current		mA	< 0.75 / 1.5mA, 100 / 230VAC, 60Hz
Remote Sense Compensation		-	HFE2500-12: 0.25V / Wire, HFE2500-24: 0.5V / Wire, HFE2500-48: 1V / Wire
Indicators		-	AC OK: Green LED, DC OK / Fail: Green / Red LED
Remote On/Off		-	Unit ON: 0 - 0.6V or short, OFF: 2 - 15V or open circuit
Parallel Operation	(1)	-	Yes, single wire current share, 95% accuracy, up to 8 units
AC Fail Signal		-	Open Collector, ON when AC is within 85 - 270VAC
DC Good Signal		-	Open Collector, ON when output is above 85 to 95% of setpoint (tracking)
Remote Adjust	(1)	-	By either external 0 - 5V signal or 1k potentiometer
I^2C Interface	(1)	-	Isolated from output, Add suffix /S, PMBus compatible
Auxiliary Output		-	11.2 - 12.5V, 0.5A, 240mV ripple and noise
Operating Temperature		°C	-10 to +70°C, derate 2%/°C from 50 to 60°C, 2.5%/°C from 60 to 70°C
Storage Temperature		°C	-30 to +85°C
Humidity (Non condensing)		%RH	Operating: 10 - 90%RH, Storage: 10 - 95%RH
Cooling		-	Two variable speed internal fans, airflow exits across input/output connector (3)
Withstand Voltage		-	I/P to O/P 3kVAC, I/P to GND 2kVAC, O/P to GND: HFE2500-12, -24V 500VAC, HFE2500-48 1.5kVAC
Isolation Resistance		MΩ	>100MΩ at 25°C & 70%RH, Output to Ground 500VDC
Vibration (Basic transportation)		-	Meets IEC60068-2-64
Shock (Basic transportation)		-	Meets IEC60068-2-27
Safety Agency Certifications		-	UL60950-1 (Listed), EN60950-1, CE Mark
Line Dip		-	Complies with SEMI F47 (200VAC line only)
Conducted and Radiated EMI		-	EN55022 & FCC part 15; Conducted class B, Radiated class A
Immunity		-	IEC61000-4-2 (lv 2,3), -3 (lv 2), -4 (lv 2), -5 (lv 3,4), -6 (lv 2), -8 (lv 4), -11
Size (W x H x D)		in	Power Supply: 4.21 x 1.61 x 12.8", Rack: 17.5 x 1.72 x 15.8"
Weight		g	Power Supply: 2100g, Rack: 5000g
Warranty		yrs	Three Years

(1) See installation manual for detailed specifications & test methods
(2) Derate linearly 1.3%/V from 100VAC to 85VAC input
(3) Reverse air - contact factory

Model Selector

Model	Output Voltage	Adjust Range(1)	Max Current (Vin>170VAC)	Max Power (Vin>170VAC)	Max Current (100<Vin<170VAC)(2)	Max Power (100<Vin<170VAC)(2)
HFE2500-12	12V	9.6 - 13.2V	200A	2400W	125A	1500W
HFE2500-12/S	12V	9.6 - 13.2V	200A	2400W	125A	1500W
HFE2500-24	24V	19.2 - 29V	104A	2496W	62A	1488W
HFE2500-24/S	24V	19.2 - 29V	104A	2496W	62A	1488W
HFE2500-48	48V	38.4 - 58V	52A	2496W	31A	1488W
HFE2500-48/S	48V	38.4 - 58V	52A	2496W	31A	1488W


Model	Load Reg	Line Reg	Ripple & Noise(1)	Efficiency (%)(4)	I²C
HFE2500-12	60mV	30mV	240mV	90 / 92%	-
HFE2500-12/S	60mV	30mV	240mV	90 / 92%	Yes
HFE2500-24	120mV	60mV	240mV	90 / 92%	-
HFE2500-24/S	120mV	60mV	240mV	90 / 92%	Yes
HFE2500-48	240mV	120mV	480mV	91 / 93%	-
HFE2500-48/S	240mV	120mV	480mV	91 / 93%	Yes

(4) At 75% load, 100 / 230VAC input

Accessories

Model	Description	Maximum Rack Current
HFE2500-S1U	Four slot 19” rack, IEC320-C20 input connector	320A each side (640A total)
HFE2500-S1U-TB	Four slot 19” rack, Terminal Block input connector	320A each side (640A total)
HFE2500/BP	One slot blanking panel, two provided with each rack	-

Outline HFE2500S1U



1	-SENSE	11	TEMP_ALM_A	21	DC_OK_A	31	NC
2	-LS	12	TEMP_ALM_B	22	DC_OK_B	32	PS_EXIST_A
3	+SENSE	13	TEMP_ALM_C	23	DC_OK_C	33	PS_EXIST_B
4	+LS	14	TEMP_ALM_D	24	DC_OK_D	34	PS_EXIST_C
5	V_RPOG	15	NC	25	NC	35	PS_EXIST_D
6	TRIM	16	AC_FAIL_A	26	SIGNAL RETURN	36	NC
7	I_PROG	17	AC_FAIL_B	27	INHIBIT_A	37	SIGNAL RETURN
8	+5V_TRIM	18	AC_FAIL_C	28	INHIBIT_B	38	+12V_AUX
9	V_REF	19	AC_FAIL_D	29	INHIBIT_C	39	ENABLE
10	-SENSE	20	NC	30	INHIBIT_D	40	SIGNAL RETURN

NOTES
1. MOUNTING HOLES FOR RACK 19". USE M6x12 SCREWS TO FIX THE UNIT TO A RACK.
2. USE NUT,FLAT WASHER AND SPRING WASHER FOR LOAD WIRES FIXING. USE LUG STUD M6 FOR LOAD WIRES.RECOMMENDED TORQUE: 42-56 Kgf.cm
3. TO FIX THE MOUNTING BRACKET TO THE CHASSIS USE M5x10 SEMS SCREWS .RECOMMENDED TIGHTENING TORQUE 27~31Kgf.cm. SCREWS MUST NOT PENETRATE THE CHASSIS MORE THAN 6.0 mm.
4. REFER TO INSTRUCTION MANUAL FOR SETTING DETAILS.
5. MODEL NAME, VOLTAGE AND CURRENT RATING AND SAFETY APPROVALS SYMBOLS WILL BE SHOWN HERE ACCORDING TO THE SPECIFICATION.
6. THE HFE-S1U RACK IS SHOWN WITH 4 HFE2500 UNITS INSTALLED.

For Additional Information, please visit
us.tdk-lambda.com/lp/products/hfe-series.htm

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TDK-Lambda:

HFE2500-12 HFE2500-24 HFE2500-48 HFE2500-S1U HFE2500-S1U-TB HFE2500-48/S HFE2500-12/S HFE2500/BP HFE2500-24/S