


Modular Phone Plugs


154-UL6234, 154-UL6236

KOBICONN









DIMENSIONS IN

SPECIFICATIONS	
USOC Type:	RJ11 (154-UL6234); RJ12 (154-UL6236)
Western Electric Type:	623 (4 or 6 Conductor for telephone to wall use)
Color:	Clear
Positions-Contacts:	6-4 (154-UL6234); 6-6 (154-UL6236)
Housing Material:	Polycarbonate (pc)
Contact Blade:	High strength copper alloy
Contact:	8% phosphor alloy
Insulation Resistance:	250VAC (max.) @ 2A 500MΩ
Dielectric Withstand Voltage:	500VAC for 1 minute
Termination Resistance:	35mΩ (max.)
Tolerance:	.006
Cable-to-Plug Tensile Strength:	20 lbs. (89N) min.
Durability:	200 mating cycles
Operating Temperature:	-40°C to +125°C

Date Last Revised: 10-15-05

Available from Mouser Electronics
1-800-346-6873
www.mouser.com

Specifications are subject to change without notice. No liability or warranty implied by this information. Environmental compliance based on producer documentation.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Kobiconn:

154-UL6234 154-UL6236