


Customer Information Sheet


DRAWING No.: M80-4000000F2-XX-XXX-00-000	SHEET 4 OF 6	IF IN DOUBT - ASK	©	NOT TO SCALE	THIRD ANGLE PROJECTION	ALL DIMENSIONS IN mm


SPECIFICATIONS:
MATERIAL:
 MOULDING: GLASS FILLED PPS, UL94V-0, BLACK
 POWER & COAX CONTACT:
  BODY = COPPER ALLOY
  INNER CONTACT,LATCHING COLLAR = BERYLLIUM COPPER
  INSULATOR = PTFE
 JACKSCREW, CIRCLIP: STAINLESS STEEL
FINISH:
 POWER & COAX CONTACT
  BODY,SLEEVE, INNER CONTACT = GOLD
  LATCHING COLLAR: = NICKEL
ELECTRICAL:
 WORKING VOLTAGE = 120V AC/DC
 VOLTAGE PROOF = 360V AC/DC
 INSULATION RESISTANCE = 100MΩ MIN
 POWER CONTACT:
  CONTACT RESISTANCE = 6mΩ MAX
  CURRENT RATING = M80-325 20A MAX 12AWG
  M80-326 15A MAX 14AWG
  M80-327 10A MAX 16AWG
  M80-32D 10A MAX 16AWG
  M80-32A 20A MAX 12AWG
  M80-32B 15A MAX 14AWG
  M80-32C 10A MAX 16AWG
  M80-328 8A MAX 18AWG
  M80-329 5A MAX 20AWG
  CONTACT AS SPECIFIED
 COAX CONTACT:
  FREQUENCY RANGE = 6GHz
  IMPEDANCE = 50 Ω
  V.S.W.R = 1.05 + (0.04 x FREQUENCY) GHz MAX
  CONTACT RESISTANCE 6 mΩ MAX
  INSULATION RESISTANCE = 10^6MΩ @250V AC
  OPERATING VOLTAGE = 180V AC @ 500mA
  MAXIMUM VOLTAGE = 1000V AC
MECHANICAL:
 DURABILITY = 500 OPERATIONS
 POWER & COAX CONTACT:
  INSERTION FORCE = 5N MAX
  WITHDRAWAL FORCE = 0.5N MIN
ENVIRONMENTAL:
 TEMPERATURE RANGE = -55°C TO +125°C
PACKING:
 BAG
FOR COMPLETE SPECIFICATION SEE COMPONENT
SPECIFICATION C005XX (LATEST ISSUE)
















M80-305/306/307
x No. OF CONTACTS




ALL COAX CONTACTS ONLY

M80-325/326/327
x No. OF CONTACTS




M80-308/309
x No. OF CONTACTS




ALL 90° COAX CONTACTS ONLY

M80-32A/32B/32C
x No. OF CONTACTS



ALL 90° POWER CONTACTS ONLY

M80-328/329
x No. OF CONTACTS



ALL POWER CONTACTS ONLY

CRIMP/SOLDER CONTACTS ONLY

DIMENSION	CALCULATION
DIM 'A'	4 x No. OF CONTACTS -4.00
DIM 'B'	4 x No. OF CONTACTS + 5.00
DIM 'C'	4 x No. OF CONTACTS + 10.00
DIM 'D'	M80-305/306/307=13.4mm
DIM 'E'	M80-325/326/327/32D=12.7mm
DIM 'F'	M80-308/309 = 9.7mm
DIM 'G'	M80-32A/32B/32C = 10.3mm
DIM 'H'	M80-328/329 = 13.9mm

EXAMPLE 1: CONNNECTOR WITH 08 COAX CONTACTS,
M80-4000000F2-08-305-00-000
DIM 'A' = 28.00mm, DIM 'B' = 37.00mm,
DIM 'C' = 42.00mm, DIM 'D' = 13.4mm
EXAMPLE 2: CONNECTOR WITH 10 POWER CONTACTS,
M80-4000000F2-10-325-00-000
DIM 'A' = 36.00mm, DIM 'B' = 45.00mm,
DIM 'C' = 50.00mm, DIM 'E' = 12.7mm

ORDER CODE:(CRIMP/SOLDER)

M80-4000000F2-XX-XXX-00-000

TOTAL No. OF CONTACTS
02 TO 12

SPECIAL CONTACTS
305 = COAX CONTACT CRIMP 2.0mm M80-305
306 = COAX CONTACT CRIMP 2.4mm M80-306
307 = COAX CONTACT CRIMP 2.7mm M80-307
308 = 90° COAX CONTACT CRIMP 2.0mm M80-308
309 = 90° COAX CONTACT CRIMP 2.7mm M80-309
325 = POWER CONTACT SOLDER 12AWG M80-325
326 = POWER CONTACT SOLDER 14AWG M80-326
327 = POWER CONTACT SOLDER 16AWG M80-327
328 = POWER CONTACT CRIMP/SOLDER 18AWG M80-328
329 = POWER CONTACT CRIMP/SOLDER 20AWG M80-329
32A = 90° POWER CONTACT SOLDER 12AWG M80-32A
32B = 90° POWER CONTACT SOLDER 14AWG M80-32B
32C = 90° POWER CONTACT SOLDER 16AWG M80-32C

NOTES:
1. CONNECTORS ARE SUPPLIED WITH CONTACTS LOOSE.
2. FOR EXTRA COAX CONTACTS, USE PART NUMBER M80-305/306/307/308/309
   FOR EXTRA POWER CONTACTS, USE PART NUMBER M80-325/326/327/328/329/32D/32A/32B/32C.
3. COAX CONTACT IS SUPPLIED AS A KIT OF PARTS: BODY, INSULATOR AND LATCHING COLLAR ARE PRE-ASSEMBLED AND SLEEVE AND INNER CONTACT ARE SEPARATE.
4. RECOMMENDED HAND CRIMP TOOL FOR COAX INNER CONTACT = Z80-292 WITH POSITIONER Z80-291 AND RECOMMENDED HAND CRIMP TOOL AND DIE SET FOR COAX SLEEVE = Z80-293.
5. RECOMMENDED HAND CRIMP TOOL FOR CONTACTS M80-328/329 = Z80-294 WITH POSITIONER Z80-295.
6. POWER AND COAX CONTACT EXTRACTION TOOL = Z80-290
7. POWER CONTACT WIRE, STRIP BY 5.00mm MINIMUM
8. INSTRUCTION SHEETS ARE AVAILABLE.
9. FOR EXAMPLE OF ALL COAX SPECIAL CONTACTS ORDER CODE SEE EXAMPLE 1 IN TABLE
10. FOR EXAMPLE OF ALL POWER SPECIAL CONTACTS ORDER CODE SEE EXAMPLE 2 IN TABLE.

SM	3	07.04.11	11222
NAME	ISS.	DATE	C/NOTE

APPROVED: S. MCCULLAGH
CHECKED: M. G. PLESTED
DRAWN: C.PENROSE
CUSTOMER REF.:
ASSEMBLY DRG:

HARWIN

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.10mm
X.XXX = ±0.01mm
ANGLES = ±5°
UNLESS STATED

MATERIAL: SEE ABOVE
FINISH: SEE ABOVE
S/AREA: mm²

TITLE: JACKSCREW DATAMATE MIXED TECHNOLOGY FEMALE ASSY WITH HEX SOCKET J/S

DRAWING NUMBER: M80-4000000F2-XX-XXX-00-000

SHT 4 OF 6


Customer Information Sheet

DRAWING No.: M80-4000000F2-XX-XXX-00-000	SHEET 5 OF 6	IF IN DOUBT - ASK	©	NOT TO SCALE	THIRD ANGLE PROJECTION	ALL DIMENSIONS IN mm


SPECIFICATIONS:
MATERIAL:
 MOULDING: GLASS FILLED PPS, UL94V-0, BLACK
 POWER & COAX CONTACT:
  BODY = COPPER ALLOY
  INNER CONTACT = BERYLLIUM COPPER
  INSULATOR = PTFE
 JACKSCREW, CIRCLIP: STAINLESS STEEL
FINISH:
 POWER & COAX CONTACT
  BODY,SLEEVE,INNER CONTACT = GOLD
ELECTRICAL:
 WORKING VOLTAGE = 120V AC/DC
 VOLTAGE PROOF = 360V AC/DC
 INSULATION RESISTANCE = 100MΩ MIN
 POWER CONTACT:
  CONTACT RESISTANCE = 6mΩ MAX
  CURRENT RATING = 20A MAX
 COAX CONTACT:
  FREQUENCY RANGE = 6GHz
  IMPEDANCE = 50 Ω
  V.S.W.R = 1.05 + (0.04 x FREQUENCY) GHz MAX
  CONTACT RESISTANCE 6 mΩ MAX
  INSULATION RESISTANCE = 10^6MΩ @250V AC
  OPERATING VOLTAGE = 180V AC @ 500mA
  MAXIMUM VOLTAGE = 1000V AC
MECHANICAL:
 DURABILITY = 500 OPERATIONS
 POWER & COAX CONTACT:
  INSERTION FORCE = 5N MAX
  WITHDRAWAL FORCE = 0.5N MIN
ENVIRONMENTAL:
 TEMPERATURE RANGE = -55°C TO +125°C
PACKING:
 TUBE
FOR COMPLETE SPECIFICATION SEE COMPONENT
SPECIFICATION C005XX (LATEST ISSUE)


NOTES:
1. FOR EXAMPLE OF ALL COAX SPECIAL CONTACTS ORDER CODE SEE EXAMPLE 1 IN TABLE
2. FOR EXAMPLE OF ALL POWER SPECIAL CONTACTS ORDER CODE SEE EXAMPLE 2 IN TABLE.

RECOMMENDED PCB LAYOUT FOR ALL POWER CONTACTS ONLY




RECOMMENDED PCB LAYOUT FOR ALL COAX CONTACTS ONLY






M80-301/302
x No. OF CONTACTS




ALL COAX CONTACTS ONLY

M80-321/322
x No. OF CONTACTS



ALL POWER CONTACTS ONLY



PC TAIL VERTICAL CONTACTS ONLY

DIMENSION	CALCULATION
DIM 'A'	4 x No. OF CONTACTS -4.00
DIM 'B'	4 x No. OF CONTACTS + 5.00
DIM 'C'	4 x No. OF CONTACTS + 10.00
DIM 'D'	M80-301 = 3.00mm, M80-302 = 4.50mm
DIM 'E'	M80-321 = 3.50mm, M80-322 = 5.00mm

EXAMPLE 1: CONNNECTOR WITH 08 COAX CONTACTS,
M80-4000000F2-08-301-00-000
DIM 'A' = 28.00mm, DIM 'B' = 37.00mm, DIM 'C' = 42.00mm
DIM'D' = 3.00mm


EXAMPLE 2: CONNECTOR WITH 10 POWER CONTACTS,
M80-4000000F2-10-321-00-000
DIM 'A' = 36.00mm, DIM 'B' = 45.00mm, DIM 'C' = 50.00mm
DIM 'E' = 3.50mm

ORDER CODE:(PC TAIL CONTACTS ONLY)
M80-4000000F2-XX-XXX-00-000

TOTAL No. OF CONTACTS
02 TO 12

SPECIAL CONTACTS
301 = COAX CONTACT PC TAIL 3.0mm M80-301
302 = COAX CONTACT PC TAIL 4.5mm M80-302
321 = POWER CONTACT PC TAIL 3.5mm M80-321
322 = POWER CONTACT PC TAIL 5.0mm M80-322

CROSS-SECTION OF COAX CONTACT



SM	3	07.04.11	11222
NAME	ISS.	DATE	C/NOTE

APPROVED: S. MCCULLAGH
CHECKED: M. G. PLESTED
DRAWN: C.PENROSE
CUSTOMER REF.:
ASSEMBLY DRG:

HARWIN

HARWIN USA	HARWIN Europe (UK)	HARWIN Asia
TEL: 603 893 5376	TEL: 023 9231 4545	TEL: +65 6 779 4909
FAX: 603 893 5396	FAX: 023 9231 4590	FAX: +65 6 779 3868
mis@harwin.com	mis@harwin.co.uk	mis@harwin.com.sg

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.10mm
X.XXX = ±0.01mm
ANGLES = ±5°
UNLESS STATED

MATERIAL: SEE ABOVE
FINISH: SEE ABOVE
S/AREA: mm²

TITLE: JACKSCREW DATAMATE MIXED TECHNOLOGY FEMALE ASSY WITH HEX SOCKET J/S

DRAWING NUMBER: M80-4000000F2-XX-XXX-00-000


SHT 5 OF 6

Customer Information Sheet


DRAWING No.: M80-4000000F2-XX-XXX-00-000	SHEET 6 OF 6	IF IN DOUBT - ASK	©	NOT TO SCALE	THIRD ANGLE PROJECTION	ALL DIMENSIONS IN mm


SPECIFICATIONS:
MATERIAL:
 MOULDING: GLASS FILLED PPS, UL94V-0, BLACK
 POWER CONTACT: COPPER ALLOY
 JACKSCREW, CIRCLIP: STAINLESS STEEL
FINISH:
 POWER CONTACT: GOLD
ELECTRICAL:
 WORKING VOLTAGE = 120V AC/DC
 VOLTAGE PROOF = 360V AC/DC
 INSULATION RESISTANCE = 100MΩ MIN
 POWER CONTACT:
  CONTACT RESISTANCE = 6 mΩ MAX
  CURRENT RATING = 20A MAX
MECHANICAL:
 DURABILITY = 500 OPERATIONS
 POWER CONTACT:
  INSERTION FORCE = 5N MAX
  WITHDRAWAL FORCE = 0.5N MIN
ENVIRONMENTAL:
 TEMPERATURE RANGE = -55°C TO +125°C
PACKING:
 TUBE
FOR COMPLETE SPECIFICATION SEE COMPONENT SPECIFICATION C005XX (LATEST ISSUE)


M80-4000000F2-12-323-00-00
SHOWN FOR ILLUSTRATION PURPOSES



PC TAIL HORIZONTAL CONTACTS ONLY







SECTION Y-Y

DIMENSION	CALCULATION
DIM 'A'	4 x No. OF CONTACTS -4.00
DIM 'B'	4 x No. OF CONTACTS + 5.00
DIM 'C'	4 x No. OF CONTACTS + 10.00
DIM 'D'	M80-323 = 3.50mm, M80-324 = 5.00mm

EXAMPLE 1: CONNECTOR WITH 10 POWER CONTACTS 3.5mm,
M80-4000000F2-10-323-00-000
DIM 'A' = 36.00mm, DIM 'B' = 45.00mm, DIM 'C' = 50.00mm
DIM 'D' = 3.50mm

EXAMPLE 2: CONNECTOR WITH 10 POWER CONTACTS 5.0mm,
M80-4000000F2-10-324-00-000
DIM 'A' = 36.00mm, DIM 'B' = 45.00mm, DIM 'C' = 50.00mm
DIM 'D' = 5.00mm


ORDER CODE:
(FEMALE HORIZONTAL POWER CONTACTS ONLY)

M80-4000000F2-XX-XXX-00-000

TOTAL No. OF CONTACTS
02 TO 12

FEMALE HORIZONTAL POWER CONTACTS
323 = POWER CONTACT PC TAIL 3.5mm M80-323
324 = POWER CONTACT PC TAIL 5.0mm M80-324

RECOMMENDED PCB LAYOUT



SM	3	07.04.11	11222
NAME	ISS.	DATE	C/NOTE

APPROVED: S. MCCULLAGH
CHECKED: M. G. PLESTED
DRAWN: C.PENROSE
CUSTOMER REF.:
ASSEMBLY DRG:

HARWIN

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.10mm
X.XXX = ±0.01mm
ANGLES = ±5°
UNLESS STATED

MATERIAL: SEE ABOVE
FINISH: SEE ABOVE
S/AREA: mm²

TITLE: JACKSCREW DATAMATE MIXED TECHNOLOGY FEMALE ASSY WITH HEX SOCKET J/S

DRAWING NUMBER: **M80-4000000F2-XX-XXX-00-000**

SHT 6 OF 6

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Harwin:

M80-4000000F2-04-327-00-000 M80-4000000F2-04-329-00-000 M80-4000000F2-08-327-00-000 M80-4000000F2-12-327-00-000